

**EU type examination certificate**  
**EU-Baumusterprüfbescheinigung**

**CE-0085BU0310**  
 Product Identification No.  
 Produkt-Identnummer

<b>Field of Application</b> <i>Anwendungsbereich</i>	EU Gas Appliances Regulation (EU/2016/426) <i>EU-Gasgeräteverordnung (EU/2016/426)</i>
<b>Owner of Certificate</b> <i>Zertifikatinhaber</i>	Ali Group S.r.l. Via Gobetti, 2a, I-20063 Cernusco sul Naviglio (MI)
<b>Distributor</b> <i>Vertreiber</i>	MARENO Ali Group S.r.l. Via Conti Agosti, 231/247, I-31010 Mareno Di Piave (TV)
<b>Product Category</b> <i>Produktart</i>	Catering appliances: Open flame burner (2101)
<b>Product Description</b> <i>Produktbezeichnung</i>	Open flame burner
<b>Model</b> <i>Modell</i>	MNBF...; MNC...; NC...
<b>Countries of Destination</b> <i>Bestimmungsländer</i>	AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR
<b>Test Reports</b> <i>Prüfberichte</i>	supplement test: 3402 A2 18 from 22.05.2019 (ING) type testing: 603/4917/1506/E01 from 11.04.2018 (FGL)
<b>Test Basis</b> <i>Prüfgrundlagen</i>	EU/2016/426 A III B (09.03.2016) DIN EN 203-1 (01.07.2014) DIN EN 203-2/1 (01.04.2015) DIN EN 203-2/2 (01.09.2006)
<b>Date of Expiry / File No.</b> <i>Ablaufdatum / AZ</i>	24.05.2028 / 18-0911-GEA

70028-04-A-CE

11.09.2019 Rie A-1/2

Date, Issued by, Sheet, Head of Certification Body  
 Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle



DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 and notified by the government of the Federal Republic of Germany for certification of gas appliances under EU Regulation

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte und von der Deutschen Bundesregierung benannte Stelle für die Zertifizierung von Gasgeräten gemäß EU-Verordnung EU/2016/426.



DVGW CERT GmbH  
 Zertifizierungsstelle

Josef-Wirmer-Str. 1-3  
 53123 Bonn

Tel. +49 228 91 88 - 888  
 Fax +49 228 91 88 - 993

www.dvgw-cert.com  
 info@dvgw-cert.com

Appliance Categories <i>Gerätekategorien</i>	Supply Pressures <i>Versorgungsdrücke</i>	Countries of Destination <i>Bestimmungsländer</i>	Remarks <i>Bemerkungen</i>
I2E	20 mbar	LU, PL	
I2EK	20/25 mbar	NL	not for appl. with 4 kW burner
I2H	20 mbar	NO	
I3+	28-30/37 mbar	LU	
I3B/P	28-30 mbar	CY, MT, NL, NO	
I3B/P	37 mbar	PL	not for appl. with 4 kW burner
II1a2H	8, 20 mbar	CH, IT	not for appl. with 4 kW burner
II2E+3+	20/25, 28-30/37 mbar	BE, FR	
II2ELL3B/P	20, 50 mbar	DE	
II2ELs3B/P	20, 13, 37 mbar	PL	not for appl. with 4 kW burner
II2H3+	20, 28-30/37 mbar	ES, GB, GR, IE, IT, PT, SK	
II2H3B/P	20, 28-30 mbar	CZ, DK, EE, FI, HR, LT, LV, RO, SE, SI, TR	
II2H3B/P	20, 50 mbar	AT, CH	
II2HS3B/P	25, 30 mbar	HU	not for appl. with 4 kW burner
II2HS3B/P	25, 50 mbar	HU	not for appl. with 4 kW burner
III1a2H3B/P	8, 20, 28-30 mbar	DK	not for appl. with 4 kW burner
III1ab2H3B/P	8, 20, 28-30 mbar	SE	not for appl. with 4 kW burner

Installation Codes <i>Installationsarten</i>	Countries of Destination <i>Bestimmungsländer</i>	Remarks <i>Bemerkungen</i>
A1	AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR	

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
MNBF78G	nominal heat input (Hi): 8,0; 7,5 (I2K) kW	nominal heat input (Hi): 8,0 kW (town gas)
MNBF712G MNC74G; NC74G; NC74GD	nominal heat input (Hi): 10,0 kW number of burners: 2 nominal heat input (Hi): max. 12,0; 11,0 (I2K) kW	nom. heat input (Hi): max. 11,0 kW (G30, 29 mbar); 10,4 kW (G30, 37 mbar); 11,6 kW (1a); 11,0 kW (1b)
NC78G; NC7FE8G; NC7FEV8G; NC78GD	number of burners: 4 nominal heat input (Hi): max. 24,0; 22,0 (I2K) kW	nom. heat input (Hi): max. 22,0 kW (G30, 29 mbar); 20,8 kW (G30, 37 mbar); 23,2 kW (1a); 22,0 kW (1b)
NC7FG8G	number of burners: 4 nominal heat input (Hi): max. 32,0; 29,5 (I2K) kW	nom. heat input (Hi): max. 30,0 kW (G30, 29 mbar); 28,8 kW (G30, 37 mbar); 31,2 kW (1a); 30,0 kW (1b)
NC712G; NC7FE12G; NC7FEV12G	number of burners: 6 nominal heat input (Hi): max. 36,0; 33,0 (I2K) kW	nom. heat input (Hi): max. 33,0 kW (G30, 29 mbar); 31,2 kW (G30, 37 mbar); 34,8 kW (1a); 33,0 kW (1b)
NC7FG12G	number of burners: 6 nominal heat input (Hi): max. 44,0; 40,5 (I2K) kW	nom. heat input (Hi): max. 41,0 kW (G30, 29 mbar); 39,2 kW (G30, 37 mbar); 42,8 kW (1a); 41,0 kW (1b)
NC7FGM12G	number of burners: 6 nominal heat input (Hi): max. 46,0; 43,0 (I2K) kW	nom. heat input (Hi): max. 43,0 kW (G30, 29 mbar); 41,2 kW (G30, 37 mbar); 44,8 kW (1a); 43,0 kW (1b)

Type Variation <i>Ausführungsvariante</i>	Explanations <i>Erläuterungen</i>
MNC...; MNBF...	modul-construction
...FG...	on gas baking oven
...FGM...	on extra large gas baking oven
...FE...	on electrical baking oven
...FEV...	on electrical baking oven with ventilation
...4...	2 open flame burner
...8...	4 open flame burner
...12...	6 open flame burner
...GD	drop in

#### Hints of Utilization /Remarks

##### Verwendungshinweise / Bemerkungen

Electrical data: 380-415 V 2N AC, 50-60 Hz, P = 6000 VA (oven); 380-415 V 2N AC, 50-60 Hz, P = 4200 VA (oven);  
220-240 V 3 AC, 50-60 Hz, P = 4200 VA (oven); 220-240 V 1N AC, 50-60 Hz, P = 1000 VA (hot cupboard)

Additionally tested appliance categories, supply pressures and countries of destination: BG: II2H3B/P (20, 28-30 mbar)